

Air to Water Heat Exchanger



Description


Order Number:	2114203
Brand Name:	SLIMLINE HEX
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection:	NEMA 12
Approvals:	CE, cURus

Technical data

Cooling capacity 95F/W50F (53 GPH):	2220 BTU
Cooling capacity 95F/W50F (132 GPH):	2560 BTU
Coolant:	Water, light oils or similar
Operating temperature range:	+34°F - +162°F
Air volume flow (system / unimpeded):	105 / 271 cfm @ 50 Hz 117 / 315 cfm @ 60 Hz
Mounting:	Wall mounted
Dimension H x W x D:	15.75 x 8.35 x 3.15 in.
Weight:	9.92 lbs
Voltage / Frequency:	400 V ~ 50/60 Hz
UL Voltage / Frequency:	400 V ~ 50/60 Hz
Starting current:	0.6 A
Max. current:	0.15 A
Max. power:	90 W
Pressure water circuit:	10 bar
Water connection:	Rp 1/4" - inside thread with 2 connectors for pipe internal diameter of 0.39 in.
Fuse:	3 x 1 A (T)
Connection:	9.8 ft cable ready for connection


Performance graph:

ΔT = Temperature difference between enclosure air and coolant
P = Cooling Capacity



Air flow:

Cut out dimensions:



Order Information

Stainless steel housing part no.	21142032
For internal mounting. Note: air outlet in floor panel!	2114202
Verpackungsmaße	538.6 x 249 x 122 mm
Bruttogewicht	6 kg
Taric code	84158300
GTIN (EAN)	5350604210141