

Air to Water Heat Exchanger



Description

Order Number: 2194000

Brand Name: 19 " RACK

Color: RAL 7035

Housing Material: Mild steel, powder coated

Ingress protection: NEMA 12

Note: With proportional waterflow regulator (control range +68°F - +122°F)


Approvals: CE

Technical data


Cooling capacity 95F/W50F (53 GPH):	6830 BTU
Cooling capacity 95F/W50F (132 GPH):	8000 BTU *)
Refrigerant / GWP:	Water, light oils or similar
Operating temperature range:	+34°F - +162°F
Air volume flow (system / unimpeded):	211 / 230 cfm @ 50 Hz 217 / 241 cfm @ 60 Hz
Mounting:	19" rack
Dimension H x W x D:	4U x 17.44 x 19.88 in.
Weight:	36.38 lbs
Voltage / Frequency:	230 V ~ 50/60 Hz
Starting current:	2.5 A
Max. current:	0.45 A
Max. power:	100 W
Pressure water circuit:	10 bar
Water connection:	.
Fuse:	4 A (T)
Short-circuit current rating:	5 kA
Connection:	Plug

Performance graph:

Delta T = Temperature difference between air intake and cooling
P = Cooling capacity



Air flow:



Order Information

Taric code	84158200
GTIN (EAN)	5350604210547